



ABB IRB 1200-7/0.7



The ABB IRB 1200-7/0.7 is a compact, high-speed, flexible robot that is ideal for machine tending and material handling applications. The IRB 1200 is proven to be 15% smaller and 10% faster than other robot in its class. The compact design allows for faster speeds while keeping precision.

The ABB IRB 1200-7/0.7 comes with a 703 mm reach and 7 kg payload. It is durable and can be mounted at any angle. The IRB 1200-7-0.7 comes with a standard IP40 protection rating, but IP67 protection is available as an option.

Advance your material handling and machine tending applications with this advanced ABB IRB 1200-7/0.7 IRC5 robot.

> For more information about the ABB IRB 1200-7/0.7, contact a Robotworx representative today at 740-251-4312.

Robot Information

Rο	hot	Sne	acifi	icat	ions
Rυ	υUι	SU	-	ιcαι	เบเเอ

Axes:..... 6

Payload:..... 7 kg

H-Reach:..... 703 mm

Repeatability: ±0.06 mm

Robot Mass: 52 kg

Structure: Articulated

Mounting: Floor, Inverted, Angle

Robot Motion Speed

Axis 1......288 °/s (5.03 rad/s)

Axis 2.....240 °/s (4.19 rad/s)

Axis 3......300 °/s (5.24 rad/s)

Axis 4......400 °/s (6.98 rad/s)

Axis 5......405 °/s (7.07 rad/s)

Axis 6.....600 °/s (10.47 rad/s)

Robot Motion Range

Axis 1.....±170°

Axis 2.....+135° - 100°

Axis 3.....+70° - 200°

Axis 4..... ±270°

Axis 5.....±130°

Axis 6.....±360°

Robot Controllers

IRC5 >

Robot Applications

Machine Tending >

Packaging >

Material Handling >

Palletizing >

Meat Processing Automation >

Pick and Place >