

FANUC M-430iA/2PH



The FANUC M-430iA/2PH robot is ideal for assembly, part transfer, and packaging. This M430iA/2PH is certified to handle foods. With its slim design and light weight, it can handle food products at fast and efficient speeds while taking up minimal space. Advance today with a FANUC M 430iA/2PH robot.

For more information about the FANUC M-430iA/2PH, contact a Robotworx representative today at 740-251-4312.

Robot Information

Robot Specifications

Axes:..... 6
 Payload:..... 2 kg
 H-Reach:..... 900 mm
 Repeatability: ±0.5 mm
 Robot Mass: 57 kg
 Structure: Articulated
 Mounting: Floor, Inverted, Angle

Robot Motion Speed

J1..... 300°/s (5.24 rad/s)
 J2..... 320°/s (5.59 rad/s)
 J3..... 320°/s (5.59 rad/s)
 J4..... 500°/s (8.73 rad/s)
 J5..... 500°/s (8.73 rad/s)
 J6..... 1700°/s (29.67 rad/s)

Robot Motion Range

J1..... ±360°
 J2..... ±230°
 J3..... ±383°
 J4..... ±380°
 J5..... ±300°
 J6..... ±540°

Robot Controllers

R-30iB >

Robot Applications

Assembly >
 Order Picking >
 Packaging >

Part Transfer >
 Pick and Place >