



FANUC M-900iB/400L



The FANUC M-900iB/400L is a long reach robot with a high payload of 400 kg! The FANUC M900iB/400L comes equipped with the advanced R-30iB controller and is ideal for a variety of applications ranging from assembly to palletizing.

This model has a wide envelope due to its 3704 mm reach. The heavy payload capacity, coupled with that long reach, allow the M900iB/400L to handle and process large parts and products, including glass panes and heavier parts, like body frame parts for vehicles.

If you are looking for a reliable robot, able to perform a variety of applications with a large payload, the FANUC M 900iB/400L R-30iB robot is a great selection.

> For more information about the FANUC M-900iB/400L, contact a Robotworx representative today at 740-251-4312.

Robot Information

Robot Specifications	Robot Motion Speed	Robot Motion Range
Axes:6	J1 80°/s (1.4 rad/s)	J1 ±360°
Payload:400 kg	J2 80°/s (1.4 rad/s)	J2 ±154°
H-Reach:3704 mm	J3 80°/s (1.4 rad/s)	J3 ±160°
Repeatability: ±0.5 mm	J4 100°/s (1.75 rad/s)	J4 ±720°
Robot Mass: 3150 kg	J5 100°/s (1.75 rad/s)	J5 ±244°
Structure: Articulated	J6 160°/s (2.79 rad/s)	J6 ±720°
Mounting: Floor		

Robot Controllers

R-30iB B-Cabinet > R-30iB iPendant Touch >

Robot Applications

Assembly >	Packaging >
Dispensing >	Palletizing >
Machine Loading >	Part Transfer >
Machine Tending >	Spot Welding >