



# FANUC R-2000iB/125L



The FANUC R-2000iB/125L is a highly reliable, long reach robot with intelligence that features a 125 kg payload and the largest work envelope in its series. This robot provides the best cost performance and ease of use for applications with integrated versatile process solutions.

Additionally, it has a slim and compact body, with a simplified, vertical articulated arm, compact wrist unit, and maintains minimum interference at the rear side. The lack of a counterweight also helps to increase the available workspace. The non-rotating forearm simplifies hose and cable dressout and also prolongs service life. Another great benefit to help increase the mean time between the failure are the fewer mechanical components that are on the robot.

> For more information about the FANUC R-2000iB/125L, contact a Robotworx representative today at 740-251-4312.

## **Robot Information**

_		_			
Ro	hot.	Sn	eciti	ıcatı	ons

Axes:.....6

Payload:.....125 kg

H-Reach:.....3005 mm

Repeatability: ±0.2 mm

Robot Mass: 1190 kg

Structure: ..... Longer Reach

Mounting: ..... Floor

#### **Robot Motion Speed**

J1..... 110°/s (1.92 rad/s)

J2..... 110°/s (1.92 rad/s)

J3..... 110°/s (1.92 rad/s)

J4..... 170°/s (2.97 rad/s)

J5..... 170°/s (2.97 rad/s)

J6..... 260°/s (4.54 rad/s)

#### **Robot Motion Range**

J1..... ±180°

J2..... +75° - 60°

J3..... +230° - 132°

J4..... ±360°

J5..... **±125**°

J6..... ±360°

#### **Robot Controllers**

R-J3iC >

R-30iA >

### **Robot Applications**

Cutting >

Fiberglass Cutting >

Foundry >

Injection Molding >

Machine Loading/Tending >

Material Handling >

Plasma Cutting >

Spot Welding >