

KUKA KR 360



The KUKA KR 360 is a heavy duty robot with a lot of options! This Kuka KR 360 KR C2 arm has a generous payload of 360 kg and a long reach of 2826 mm. The KR 360 Kuka robot can be floor or ceiling mounted to allow for effective use of existing floorspace.

A foundry version of the KR 360 KR C2 is available for volatile conditions. These variants are heat and water resistant. The Kuka KR 360 heavy duty robot is highly adaptable to cleanroom use and other ambient conditions.

For more information about the KUKA KR 360,
contact a Robotworx representative today at 740-251-4312.

Robot Information

Robot Specifications

Axes:..... 6
Payload:..... 360 kg
H-Reach:..... 2826 mm
Repeatability: ± 0.15 mm
Robot Mass: 2350 kg
Structure: Articulated
Mounting: Floor, Inverted

Robot Motion Speed

J1.....89 °/s (1.55 rad/s)
J2.....89 °/s (1.55 rad/s)
J3.....93 °/s (1.62 rad/s)
J4.....109 °/s (1.9 rad/s)
J5.....112 °/s (1.95 rad/s)
J6.....157 °/s (2.74 rad/s)

Robot Motion Range

J1.....±185°
J2.....+110° - 40°
J3.....+60° - 184°
J4.....±350°
J5.....±118°
J6.....±350°

Robot Controllers

KUKA KR C2 >

Robot Applications

Assembly Robots > Material Handling Robots >
Coating Robots > Order Picking Robots >
Fiberglass Cutting Robots > Packaging Robots >
Foundry Robots > Paint Robots >



www.robots.com



370 W. Fairground St. Marion, OH 43302



1-740-383-8383