

KUKA KR 140 KR



Available with three different payloads and work envelopes, the Kuka KR 140 model is durable and accurate.

The KR 140 KRC2 robot is comfortable in many settings, from general industry to automotive manufacturing. Cost-saving and hard-working, the KR 140 KR C2 transforms production.

For more information about the KUKA KR 140 KR, contact a Robotworx representative today at 740-251-4312.

Robot Information

Robot Specifications

Axes:..... 6
 Payload:..... 140 kg
 H-Reach:..... 2400 mm
 Repeatability: ± 0.15 mm
 Robot Mass: 2400 kg
 Structure: Articulated
 Mounting: Floor

Robot Motion Speed

J1.....100 °/s (1.75 rad/s)
 J2.....100 °/s (1.75 rad/s)
 J3.....100 °/s (1.75 rad/s)
 J4.....156 °/s (2.72 rad/s)
 J5.....171 °/s (2.98 rad/s)
 J6.....241 °/s (4.21 rad/s)

Robot Motion Range

J1.....±185°
 J3.....+148° - 120°
 J4.....±350°
 J5.....±120°
 J6.....±350°

Robot Controllers

KUKA KR C4 >

Robot Applications

- Assembly Robots >
- Coating Robots >
- Fiberglass Cutting Robots >
- Machine Loading Robots >
- Material Handling Robots >
- Meat Processing Automation >
- Order Picking Robots >
- Packaging Robots >