

KUKA KR 60 L16-2 KS



The KR 60 L 16-2 KS is a swift, efficient, and tireless worker that handle up to 16 kg in payload and has a long reach of up to 2952 mm!

The KR 60 L 16-2 KS is the perfect solution for any application that requires something that can tackle hard to reach places. It is a shelf mounted, long reach robot that has a slim arm to easily reach into those tight spaces, especially a vehicle body. Once inside the body, this arm can precisely carry out a variety of functions such as the consistent application of adhesives or sealants.

It is paired with the KR C4 controller and ready to help provide a consistent, quality tool for those slim spaces!

For more information about the KUKA KR 60 L16-2 KS,
contact a Robotworx representative today at 740-251-4312.

Robot Information

Robot Specifications

Axes:..... 6
Payload:..... 16 kg
H-Reach:..... 2952 mm
Repeatability: ± 0.06 mm
Robot Mass: 650 kg
Structure: Articulated
Mounting: Floor

Robot Motion Speed

J1.....103 °/s (1.8 rad/s)
J2.....88 °/s (1.54 rad/s)
J3.....81 °/s (1.41 rad/s)
J4.....230 °/s (4.01 rad/s)
J5.....165 °/s (2.88 rad/s)
J6.....249 °/s (4.35 rad/s)

Robot Motion Range

J1..... $\pm 150^\circ$
J2..... $+75^\circ - 115^\circ$
J3..... $+158^\circ - 120^\circ$
J4..... $\pm 350^\circ$
J5..... $\pm 130^\circ$
J6..... $\pm 350^\circ$

Robot Controllers

KUKA KR C4 >

Robot Applications

Coating Robots >

Cutting Robots >

Machine Loading Robots >

Machine Tending Robots >

Material Handling Robots >

Order Picking Robots >

Packaging Robots >

Paint Robots >