



KUKA KR 10 R1100 Sixx



High speeds and incredible precision are huge attributes of the KR 10 R1100 Sixx. Tackling a variety of applications, this robot is very versatile with floor, ceiling, and wall mounting options. It has an IP54 protection rating, payload capacity of 10 kg, and 1101 mm reach.

If your job requires a robot that can withstand harsh conditions, then consider the KR 10 R1100 Sixx WP model. This robot's plastic parts are replaced by stable stainless stell covers. There are additional seals on the interior and surface treatments that add a level of resistances and strength. Additionally, it has a higher protection rating; IP67.

Both robots will be paired with the KR C4 Compact controller.

For more information about the KUKA KR 10 R1100 Sixx, contact a Robotworx representative today at 740-251-4312.

Robot Information

Robot Specifications	Robot Motion Speed	Robot Motion Range
Axes: 6		
Payload: 10 kg		
H-Reach: 1101 mm		
Repeatability: ± 0.03 mm		
Robot Mass: 54 kg		
Structure: Articulated		
Mounting: Floor, Inverted, Angle		
Robot Controllers	Robot Applications	
Robot Contioners	Robot Applications	
KUKA KR C4 Compact >	Assembly Robots >	Material Handling Robots >
	Cutting Robots >	Palletizing Robots >
	Machine Loading Robots 🗦	