



Motoman MA3120



The Motoman MA3120 one of the latest Motoman arc welding robots. With a slim design, this high speed robot has a 6 kg payload, 3121 mm horizontal reach and 5615 mm vertical reach.

With that extra long reach, there is no need to lay down tracks for the robot to move on, which improves the versatility of the layout design for manufacturers. The extended reach of the MA3120 allows it to manipulate larger work pieces, especially for industries like the agriculture, automotive, and construction industries.

The Motoman MA3120 comes equipped with the DX200 controller. If you are looking for a reduced cycle time, high quality welds, and a robot you can depend on, the Motoman MA3120 DX200 is an excellent choice.

> For more information about the Motoman MA3120, contact a Robotworx representative today at 740-251-4312.

Robot Information

_		_			
Ro	bot	Sno	ecit	ıcatı	ions

Axes:..... 6

Payload:..... 6 kg

H-Reach:...... 3121 mm

Repeatability: ±0.08 mm

Robot Mass: 501 kg

Structure: Articulated

Mounting: Floor

Robot Motion Speed

S-Axis.....180 °/s (3.14 rad/s)

L-Axis.....178 °/s (3.11 rad/s)

U-Axis.....178 °/s (3.11 rad/s)

R-Axis.....400 °/s (6.98 rad/s)

B-Axis.....430 °/s (7.5 rad/s)

T-Axis.....630 °/s (11 rad/s)

Robot Motion Range

S-Axis.....±180°

L-Axis.....+135° - 90°

U-Axis.....+251° - 160°

R-Axis.....±150°

B-Axis.....+90° - 135°

T-Axis.....±210°

Robot Controllers

DX200 >

Robot Applications

Arc Welding >

Welding Automation >