



## **Motoman DA20**



The Motoman DA20 robot offers 13 axes of motion (six in each arm and one single axis for base rotation), resulting in human-like movements. With a 20 kg payload for each arm, the DA20 NX100 is perfect for applications such as assembly, machine tending, packaging, and other material handling tasks.

The Motoman DA20 NX100 robot is controlled by a Motoman NX100 robot controller that directs movement of each axes of the robot.

> For more information about the Motoman DA20, contact a Robotworx representative today at 740-251-4312.

## **Robot Information**

Robot Specifications	Robot Motion Speed	Robot Motion Range
Axes: 13	S-Axis170 °/s (2.97 rad/s)	S-Axis+190° - 80°
Payload: 20 kg	L-Axis170 °/s (2.97 rad/s)	L-Axis <b>+230° - 30°</b>
H-Reach: 765 mm	U-Axis170 °/s (2.97 rad/s)	U-Axis <b>+215° - 35°</b>
Repeatability: ±0.1 mm	R-Axis300 °/s (5.24 rad/s)	R-Axis±180°
Robot Mass: kg	B-Axis <b>300 °/s (5.24 rad/s)</b>	B-Axis±120°
Structure: Articulated	T-Axis <b>580 °/s (10.12 rad/s)</b>	T-Axis <b>±180°</b>
Mounting: Floor		
Robot Controllers	Robot Applications	
NX100 >	Assembly >	Packaging >
	Machine Tending >	Part Transfer >
	Material Handling >	