



Motoman HP6RS



The Motoman HP 6RS is the short-arm, shelf mount variation. The Motoman HP6RS NX100 robot allows a larger work area because it has the ability to reach under and behind the robot body.

RobotWorx experts also take pride in their refurbished robots to include the used Motoman HP6RS. The used HP6RS provides owners with the same benefits of a new one, as it has undergone a complete reconditioning process, bringing it back to like-new condition. Furthermore, any purchase of a used Motoman HP6RS includes the RobotWorx Value Package.

> For more information about the Motoman HP6RS, contact a Robotworx representative today at 740-251-4312.

Robot Information

_		_			
Ro	bot	Sno	ecit	ıcatı	ions

Axes:..... 6

Payload:..... 6 kg

H-Reach:..... 1147 mm

Repeatability: ±0.08 mm

Robot Mass: kg

Structure: Articulated

Mounting: Floor

Robot Motion Speed

S-Axis.....180 °/s (3.14 rad/s)

L-Axis.....220 °/s (3.84 rad/s)

U-Axis.....220 °/s (3.84 rad/s)

R-Axis.....340 °/s (5.93 rad/s)

B-Axis.....340 °/s (5.93 rad/s)

T-Axis.....520 °/s (9.08 rad/s)

Robot Motion Range

S-Axis.....+135° - 120°

L-Axis.....+90° - 130°

U-Axis.....+94° - 185°

R-Axis.....±180°

B-Axis.....±135°

T-Axis.....±360°

Robot Controllers

NX100 Teach Pendant >

Robot Applications

Machine Tending >

Dispensing >

Material Handling >