



Motoman ES200TD



If your company is looking for a material handling gantry robot, the Motoman ES200TD may be the right choice for your needs. The ceiling-mounted ES200TD saves the space on the factory floor. The ES200TD DX100 is a high-performance robot equipped to handle heavy payload machine or press tending, as well as other handling tasks.

The six-axis, high-speed ES200TD DX100 enhances the versatility of your processes with a large work envelope, and the slim design decreases cycle times and increases productivity.

Motoman also offers a shelf-mounted option (ES200RD) and a floor-mounted version (ES200D), giving you a choice of which mounting option works best for your company.

> For more information about the Motoman ES200TD, contact a Robotworx representative today at 740-251-4312.

Robot Information

Robot Specifications	Rob
Axes: 6	S-A
Payload: 200 kg	L-A:
H-Reach: 2416 mm	U-A
Repeatability: ±0.2 mm	R-A
Robot Mass: 1150 kg	B-A
Structure: Articulated	T-A:
Mounting: Inverted	

Robot Motion Speed	Robot Motion Range
S-Axis 95 °/ s (1.66 rad/s)	S-Axis+180° - 180°
Axis 90 °/s (1.57 rad/s)	L-Axis+50° - 50°
J-Axis 95 °/ s (1.66 rad/s)	U-Axis +220° - 125°
R-Axis 120 °/ s (2.09 rad/s)	R-Axis+360° - 360°
3-Axis 120 °/ s (2.09 rad/s)	B-Axis+125° - 125°
T-Axis 190°/s (3.32 rad/s)	T-Axis +360° - 360°

Robot Controllers

DX100 >

Machine Tending >	Press Tending >
Material Handling >	

Robot Applications