



Motoman MH50-35



The Motoman MH50-35 industrial robot provides a much larger working envelope. While the payload capacity has been reduced, the MH50-35 DX100 still features a generous 35 kg payload and high-performance motors for maximum performance. There are used MH50-35 robots also available for sale. Every used Motoman MH50-35 has undergone a very meticulous refurbishment process and includes the RobotWorx Value Package.

The new and used MH50-35 are both compatible with the DX100 controller for optimum performance.

For more information about the Motoman MH50-35, contact a Robotworx representative today at 740-251-4312.

Robot Motion Range

L-Axis.....+135° - 90°

U-Axis.....+296° - 160°

S-Axis.....**±180°**

R-Axis.....**±360°** B-Axis.....**±125°**

T-Axis.....**±360°**

Robot Information

Robot Specifications

Robot Controllers

DX100 >

Robot Motion Speed

S-Axis.....180 °/s (3.14 rad/s) L-Axis.....140 °/s (2.44 rad/s) U-Axis.....178 °/s (3.11 rad/s) R-Axis.....250 °/s (4.36 rad/s) B-Axis.....250 °/s (4.36 rad/s) T-Axis.....360 °/s (6.28 rad/s)

Robot Applications

Coating > Dispensing > Fiberglass Cutting > Material Handling > Material Removal > Part Transfer > Pick and Place >